

KWO® Universal HD – ePTFE gasket tape


 MADE IN GERMANY

KWO® Universal HD is gasket tape of mono-directionally expanded pure PTFE with a high density.

The tape is characterised by a rectangular cross-section and a relatively small width. The high density of the material and the special cross-section of the tape allow the sealing of very uneven sealing surfaces even at a low gasket stress.

KWO® Universal HD sealant tape is suitable for delicate sealing applications on surfaces vulnerable to tension, such as glass or ceramics. The tape can also be used to seal weak flanges subject to considerable deformation, for example glass reinforced plastics (GRP), plastic fittings and ventilation facilities.



★ Advantages

- > low diffusion leakage
- > excellent adaptability to all surfaces
- > easy filling of flange gaps
- > harmless for food-contact applications

⚙ Properties

- > UV resistant; non-ageing
- > nontoxic, biologically inert
- > non-flammable

📦 Applications

- > flange connections, tank sealings
- > ventilation systems
- > apparatus constructions
- > machine housings
- > pumps, food processing systems

📜 Certificates

- > certificated and monitored by TÜV
- > FDA 21 CFR 177.1550 compliant
- > EC 1935/2004 - suitable for food applications

TECHNICAL DATA

Material	100 % expanded PTFE (ePTFE) - self-adhesive
Chemical resistance	pH range from 0 to 14; full chemical resistance (except molten alkali metals and elemental fluorine)
Temperature range	-268°C (-450°F) up to +270°C (+518°F), short-term +315°C (+600°F) recommended temperature range: from -200°C (-328°F) to +150°C (302°F)*
Pressure resistance	vacuum up to 80bar (1160psi) depending on the installation situation*
Physiologically inert	physiologically harmless in all recommended applications
Density	1,00 g/cm ³ +/-10%

* Note: temperature and pressure guides cannot necessarily be used simultaneously.


Quality assurance

The KWO Quality Management is certified according to DIN EN ISO 9001. Our suppliers are also integrated in this quality system. We use exclusively high quality raw materials in the fabrication of our products, which provide the highest level of safety and reliability.




Teflon™ is a trademark of The Chemours Company FC, LLC used under license by KWO Dichtungstechnik GmbH.

Available Dimensions

Width x Thickness* [mm]	Spool length [m]		
	10	25	50
4x2,5	X	X	X
6x4,6	X	X	X
8x5,5	X	X	
10x7	X	X	
14x5	X		



*Other dimensions available on request.


To order, please use the following text

KWO® Universal HD, __ x __ mm - __ m, quantity in meter
 (width) (thickness) (spool length)

The p-T diagram indicates the service limits considering the simultaneous influence of pressure and temperature.

- Range 1: Typical service limits
- Range 2: Maximum application limits, after technical verification



- ✓ Made in Germany
- ✓ International Presence
- ✓ Represented in over 46 countries

For detailed selection criteria, technical information, installation guideline and the relevant contact person, please visit our website: www.kwo-ptfe.de

KWO Dichtungstechnik GmbH

Am Eschengrund 3
 83135 Schechen, Germany
 Tel: + 49 8039 90254-0
 Fax: + 49 8039 90254-299
 Email: info@kwo-ptfe.de



All technical information and advice given here is based on our previous experiences and/or test results. We give this information to the best of our knowledge, but assume no legal responsibility. Customers are asked to check the suitability and usability in the specific application, since the performance of the product can only be judged when all necessary operating data are available. Specifications are subject to change without notice. KWO's terms and conditions of sale apply to the purchase and sale of the product.